

BELLA

3CCT FIRE RATED DOWNLIGHT



Bella is a 6W IP65 fire-rated LED downlight with three CCT options: 3000K, 4000K, and 6500K. It's designed for both living spaces and bathrooms, featuring a modern white trim, dimmable, push-fit terminals with loop-in/loop-out capabilities and is Fire rated for both standard timber joist and I-joist ceiling construction. It is a quality, reliable, energy efficient lighting solution.



Features

- Selectable 3CCT - 3000 | 4000 | 6500K
- Fire-rated: I-joist - 30/60/90mins, Solid timber joist - 30mins, Metal Web joist - 30mins
- Acoustic-rated
- Optional interchangeable bezels
- Push-fit terminals with loop-in/loop-out capabilities
- IP65 from the front making it ideal for bathrooms as well as living spaces

| Code | Description | Lumen Output | Emergency Lumen Output | Wattage | Efficacy |
|---------|---|--------------|------------------------|---------|----------|
| BA/W | Bella Fire Rated Downlight 6W 3CCT | 660lm | - | 6W | 110 lm/W |
| BA/10/W | Bella 10 Contractor Pack Fire Rated Downlight 6W 3CCT | 660lm | - | 6W | 110 lm/W |


BELLA

3CCT FIRE RATED DOWNLIGHT

Specification

| | |
|-----------------------------|--------------------------------------|
| Material:- | Housing: Steel, Bezel: Polycarbonate |
| Warranty:- | 3 Years |
| Colour Temperature:- | 3CCT Selectable 3000K/4000K/6500K |
| IP Rating:- | IP65 (from below ceiling) |
| LED Lifetime:- | L70B50 30,000 Hours |

| | |
|------------------------------|---------------|
| CRI:- | Ra >80 |
| Working Temperature:- | -20°C to 25°C |
| Beam Angle:- | 60° |
| Power Factor:- | >0.7 |



www.redarrowelectrical.co.uk