

STELLAR TILT

4CCT FIRE RATED TILT DOWNLIGHT

Stellar Tilt extends the popular Stellar range, with the addition of tilt adjustment. From highlighting art to washing walls, this fire rated downlight features selectable 4CCT colour temperature which can be changed without removing from the ceiling, plus a wide range of optional colour finish bezels in round and square format.



Features

- Improved Speed Terminal Block & EM Loop
- Selectable 4CCT - 2700 / 3000 / 4000 / 6000K, operated from below the ceiling
- Fire rated to EN1365-2:2014 / BS476-21:1987 for standard timber and i-joist construction
- Optional circular and square interchangeable bezels
- Elegant 20° tilting inner bezel for directional light

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
SR/T/W	Stellar Tilt Fire Rated Downlight IP65 White 6W 4CCT 2700/3000/4000/6000K	775lm		6W	129 lm/W

Product Information

Warranty	5 Years
Colour Appearance (CCT)	2700K 3000K 4000K 6000K
IP Rating	IP65 (from below ceiling)
Voltage	220-240V
Material (Body/Housing)	Steel
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80
Colour Finish	White RAL9003

LED Life Expectancy	L70B50 50,000 Hours
Power Factor	>0.85
Frequency	50/60Hz
Driver Type	Dimmable
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	-20°C to 40°C

STELLAR TILT

4CCT FIRE RATED TILT DOWNLIGHT

Packaging Information

Dimensions (mm)	Ø: 100 x D: 42 mm
Product Net Weight (kg)	0.338 kg
Barcode	5055807624800
Box Dimensions (mm)	L: 103 x W: 103 x D: 82 mm
Box Gross Weight (kg)	0.39 kg

Units/Outer Carton	50
Outer Carton Barcode	15055807624807
Outer Carton Dimensions (mm)	L: 530 x W: 530 x D: 179 mm
Outer Carton Gross Weight (kg)	17.9 kg

