



Profile



Part of the Cabinet and Bathroom Fittings product category

Model	Profile Razor PRO
Code	APRP/1
Application	Healthcare, Hospitality, Residential

GENERAL INFORMATION

Input	220-240V
Wattage	4W - 8W
Operating Temp	0°C to 40°C
Lumens Delivered	100lm - 400lm (4000K)
lm/W	50lm/W
CCT	3000K/4000K/5000K
UGR	22
Beam Angle	60/80

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.92 kg
Colour / Finish	White
Height	70 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Wall
Power Factor	0.75
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Ultra-slim unobtrusive modern dual voltage LED bathroom light suitable for residential, hospitality and healthcare applications
- Directional light output provides optimum facial illumination
- Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire
- Easy lift hatch for quick and effortless maintenance
- Fast wire connection for a hassle-free installation process





Profile



Part of the Cabinet and Bathroom Fittings product category

Model	Profile Razor PRO
Code	APRP/1
Application	Healthcare, Hospitality, Residential

