

# SLFM360N

## PIR Presence Detector (Flush Mount)

### Features & Benefits

- Slimline sensor head design
- 360° detection zone for optimum coverage
- IP44 weatherproof rating (internal use only)
- Manual override (Pulse) for extended light on times
- Adjustable time setting
- Adjustable LUX setting
- 75mm diameter ceiling cut-out



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP44
Setting Type	Dial
Approved Mounting Height (m)	2.5
Presence Detection (m)	4 Diameter
Motion Detection (m)	8 Diameter
Detection Angle	360°
Hole Cut-Out Size (mm)	75
Standby Consumption	<0.5W

# Data sheet

## SLFM360N

Light / PIR Presence Detectors

Number Of Channels	1
Switch Rating	500W LED (PF>0.9), 2000W Halogen, 500W Fluorescent, 75W Fan
ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
LUX Level	1 to 1000
Detection Range (m)	8 Diameter
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 8 Units In Parallel
Cable Entry(s)	Back Entry
Accessories (Included)	Terminal Cover
Dimensions	Height 90mm, Width 90mm, Depth 60mm

### General

Weight (g)	90
Height (mm)	90
Width (mm)	90
Depth (mm)	60
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Terminal Cover
EAN Number	5012483014790
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

# Data sheet

## SLFM360N

Light / PIR Presence Detectors

### Line Diagrams

